

CI/SfB

| (57.7) | | |

1st Edition



Lo-Carbon Solo Plus®/SELV - Up to 70% Energy Saving

Lo-Carbon Residential Range

**Vent-Axia®
Lo-Carbon™**

Lo-Carbon Solo Plus®/SELV

Features & Benefits

- Up to 70% energy saving
- Filter less as standard - innovative impeller design means no need for a filter
- Integral Lo-Carbon power supply
- Meets current Building Regulations Approved Documents F & L
- IPX4 rated - IPX7 rated (SELV)
- Flush or surface mountable
- Adjustable rear or side exit spigot
- Lo-Carbon Solo Plus SELV is suitable for installation over or within reach of a shower or bath
- Extremely low sound levels
- 5 Year Motor Guarantee
- Suitable for wall, ceiling and panel mounting
- SELV Models - Supplied with a remote transformer

Long Life Ventilation

The Lo-Carbon Solo Plus range from Vent-Axia has been specially designed for through the wall and ducted applications, suitable for internal bathrooms, toilets and other small rooms. Finished in white, the Lo-Carbon Solo Plus can be flush or surface mounted, with a 2 position 100mm circular spigot for rear entry or connecting to a vertical ducting system. The powerful centrifugal impeller allows installations using 100mm ducting in straight runs up to 50m, whilst still achieving 15l/s as required by Building Regulations Approved Document F.

Continuous running products, such as the Solo Plus, installed in all wet areas of a dwelling are classed as a wholehouse ventilation system and therefore only need to move the amount of air as laid down in table 5.1a and 5.1b of Building Regulations Approved Document F.

The Lo-Carbon Solo Plus has an adjustable boost speed which is set at installation variable between a wall or duct setting for boost/override operation to meet Building Regulations thus ensuring minimum

energy usage and low sound levels. All models have an optional speed for constant trickle ventilation (12l/s), selectable at installation. Depending on the model, the fan will switch from trickle (if selected) to boost via the pullcord/light switch/humidity sensor/PIR.

All models can be wall, panel or ceiling mounted and can be connected to either circular, rectangular or Vent-Axia's flat ducting. Enclosure of the electrical components is manufactured from flame retardant grade material.

Safety Extra Low Voltage Fan (SELV)

Designed for areas where a fan has to be fitted over or within Zone 1 in a room containing a fixed bath or shower according to IEE wiring regulations (BS 7671), the Lo-Carbon Solo Plus SELV fan can be safely installed within the spray area. The fan is rated IPX7. Control is by mains safety isolating transformer unit with 24V DC SELV output, which is sited away from any source of spray and out of reach of a person using a fixed bath or shower. Controller Supply voltage 220-240V/1/50Hz. Output to fan SELV 24V DC.

Models

Lo-Carbon Solo Plus/SELV P (Pullcord)

Flush or surface mountable. Control by Pullcord. 2 Speed. Constant trickle option. Adjustable boost. In-built Lo-Carbon controller.

Model	Stock Ref
P	427481
SELV P	427485

Lo-Carbon Solo Plus/SELV T (Timer)

Flush or surface mountable. Control by room light or switch. 2 Speed. Constant trickle option. Adjustable boost. Adjustable timer overrun. Delay on timer. In-built Lo-Carbon controller.

Model	Stock Ref
T	427482
SELV T	427486

Lo-Carbon Solo Plus/SELV HT (Humidistat-Timer)

Flush or surface mountable. Humidity controlled fan with override pullcord. Constant trickle option. Adjustable boost. Adjustable timer overrun. Delay on timer. Adjustable humidity sensor. In-built Lo-Carbon controller. Hour Run Meter as standard on all Lo-Carbon humidity controlled Solo Plus fans.

Model	Stock Ref
HT	427483
SELV HT	427487

Lo-Carbon Solo Plus/SELV TM (Timer/PIR)

Flush or surface mountable. Control by integral PIR detector. 2 Speed. Constant trickle option. Adjustable boost. In-built Lo-Carbon controller.

Model	Stock Ref
TM	427484
SELV TM	427488

Lo-Carbon Solo Plus Bezel

Used when flush mounting - reduces the need to make good.

Stock Ref
404106

Wall Kit

Stock Ref
254102 (White)
254100 (Brown)


Filter pack (1 per pack)

The design of the Solo Plus means that it does not need a filter. However, if you are going to install the product in a heavily greasy environment, you may want to protect the product by fitting a filter.

Stock Ref
449265



Dimensions (mm)




A	B	C	D	∅
263	224	106	55	98
F	G	H	I	J
62	65	98	21	34

SELV Transformer: (W x H x D) 147 x 88 x 50mm.

Weight 2.2kg, SELV Weight 2.7kg.

Lo-Carbon SELV controller demotions: (W x H x D) 87x87x33mm.

Performance Curve (Duct Mode)



Performance Guide

Model		Extract Performance l/s (m³/h)			Power consumption - watts			dB(A) @ 3m			SFP (W/l/s) @ OPa
		Boost	High trickle	Low Trickle	Boost	High trickle	Low Trickle	Boost	High trickle	Low Trickle	
Lo-Carbon Solo Plus/SELV P/T/HT/TM	Wall mode	18 (64.8)	12 (43.2)	8 (28.8)	6	2.9	2.3	33.5	27	23.5	0.33
	Duct mode	21 (75.6)	17 (61.2)	11 (39.6)	8.4	5.3	3.2	35.5	33	26	0.40

Tested at 240VAC @ 50Hz



By Appointment to H.M. The Queen
Suppliers of Unit Ventilation Equipment
Vent-Axia, Crawley, West Sussex

Vent-Axia®

VENT-AXIA CONTACT NUMBERS

Free technical, installation and sales advice is available


Sales Centre:

Domestic & Commercial

Sales Tel:	0844 856 0590
Sales Fax:	01293 565169
Tech Support Tel:	0844 856 0594
Tech Support Fax:	01293 539209

Supply & Service

All sales made by Vent-Axia Limited are made only upon the terms of the Company's Conditions of Sale, a copy of which may be obtained on request. As part of the policy of continuous product improvement Vent-Axia reserves the right to alter specifications without notice.



A British company supporting British manufacturing
Vent-Axia Group Ltd Products you can trust